

# Arbit TRUST Gateway

Whitepaper

Release 2016-03-01


Arbit technical reference:  
Rasmus Borch  
rasmus.borch@arbit.dk

## Hardware

The Arbit TRUST Gateway (ATG) is a more advanced type of data diode with release capability. It is able to verify data requested to pass through originates from an approved source system using digital signing technology.

The ATG is based on three separated networks connected by data diodes. The data diodes ensures that data is only able to be transmitted in one direction. This is done by using a single fiber optic cable to transmit the data with no return flow possible<sup>1</sup>.

The two data diodes creates an isolated network with no interactive access from neither the sending nor the receiving net. This isolated network (called the VOID net) handles the verification of the data that is requested to pass through the ATG. Each approved source system allowed to transmit data through the ATG will sign the data to be released. The ATG then checks the signature on the VOID net. If the signature is correct the data may optionally be required to be released manually by a releasing officer before passing through. Otherwise the event is logged and possible counter measures may take effect.



The basic platform of the ATG consist of four units:

High Guard	(1U enclosure; Sending net)
VOID Proxy	(1U enclosure; VOID net)
VOID Guard	(1U enclosure; VOID net)
Low Proxy	(1U enclosure; Receiving net)

### Technical specifications (complete platform)

Diode principle	Hardware based (one way laser light)
Backflow	None (secured by the laws of physics)
Diode NIC	4x
Single fiber	2x
Diode NIC speed	Gigabit
Server type	4x Embedded computers (quad-core)
Server storage	Disk-less system (runs directly from 4 custom configured CDs created at the operation site)
Power supply	8x (universal; redundant power supplies for all units)
Server size	4x 1U
Weight	4x 15 kg
Network connectors	4x RJ45 (gigabit; 1x sending network; 2x VOID net; 1x receiving network)
KVM	Default not included (listed in quote if added)
TEMPEST level	Up to level A (optional)

### Technical specifications (each unit: High Guard, VOID Proxy, VOID Guard, LOW Proxy)

Connectors	1x Diode (Fiber), 1x Network (RJ45 or fiber), 1x CD-ROM, 1x SmartCard Reader, 1x VGA, 1x USB (keyboard only)
Server type	Embedded computer (quad-core; 16 GB RAM)
Server storage	1 CD with software, 1 SmartCard with configuration
Power supply	2x (universal; redundant power supply)
Server size	1U x 19" wide x 40" deep
Weight	20 kg
TEMPEST level	Up to level A (optional)

<sup>1</sup> Please refer to the Arbit Data Diode whitepaper for more information on the design of Arbit Data Diode technology.

## Software

The following main software products are installed on both pitcher and catcher:

ATG software	Arbit TRUST Gateway software
OS	Debian Linux (minimal Ubuntu Server 64-bit v14.04)
Terminal access	OpenSSH Server (optional)
Open system	Yes (may be inspected and customized by customer)

## Arbit TRUST Gateway software

The license includes the following software features:

Manual release from VOID net terminal	Yes (optional; otherwise automatic)
Automatic release (no manual check)	Yes (optional; otherwise manual)
Signature check of all data	Yes
Complete transaction log (including free-text search)	Yes (add-on)
External content verifiers	Yes (add-on; file type identification/filter provided by Arbit)
External content verifiers created by customer	Yes (uses open API)
Latency	<10 sec for transactions up to 10 MiB
Max transaction size	4 GB
Source system integration	Open Java API
Configuration and key generation	Stand-alone laptop
Running configuration changeable	No (new runnable CDs must be created on site)
Multiple approved source systems possible	Yes
Regular maintenance	None (the system runs unattended)

## Data Integrity

The ATG utilizes several layers of data integrity:

- 1) The transport is based on UDP which includes a checksum ensuring that the individual packages are not corrupted.
- 2) On top of the UDP transport the data diode maintains strict transaction control which is able to detect any lost packages and which ensures that all packages are processed in the correct order.
- 3) Finally the ATG uses a redundancy algorithm which prevents almost all network transmission errors.